

Package ‘spatsoc’

January 10, 2019

Title Group Animal Relocation Data by Spatial and Temporal Relationship

Version 0.1.6

Description Detects spatial and temporal groups in GPS relocations. It can be used to convert GPS relocations to gambit-of-the-group format to build proximity-based social networks. In addition, the randomizations function provides data-stream randomization methods suitable for GPS data.

Depends R (>= 3.4)

License GPL-3 | file LICENSE

Encoding UTF-8

LazyData true

Imports data.table (>= 1.10.5), sp, rgeos, adehabitatHR, igraph, methods

Suggests testthat, knitr, rmarkdown, asnipe

SystemRequirements GEOS (>= 3.2.0)

RoxygenNote 6.1.0

VignetteBuilder knitr

BugReports <https://github.com/ropensci/spatsoc/issues>

URL <https://spatsoc.gitlab.io>, <https://github.com/ropensci/spatsoc>

NeedsCompilation no

Author Alec L. Robitaille [aut, cre] (<<https://orcid.org/0000-0002-4706-1762>>),
Quinn Webber [aut] (<<https://orcid.org/0000-0002-0434-9360>>),
Eric Vander Wal [aut] (<<https://orcid.org/0000-0002-8534-4317>>)

Maintainer Alec L. Robitaille <robit.alec@gmail.com>

Repository CRAN

Date/Publication 2019-01-10 18:10:03 UTC

R topics documented:

build_lines	2
build_polys	4
DT	6
get_gbi	6
group_lines	7
group_polys	10
group_pts	12
group_times	13
randomizations	15
spatsoc	18
Index	20

build_lines	<i>Build Lines</i>
-------------	--------------------

Description

build_lines creates a SpatialLines object from a data.table. The function accepts a data.table with relocation data, individual identifiers a sorting column and a projection. The relocation data is transformed into SpatialLines for each individual and optionally, each splitBy. Relocation data should be in two columns representing the X and Y coordinates.

Usage

```
build_lines(DT = NULL, projection = NULL, id = NULL, coords = NULL,
            sortBy = NULL, splitBy = NULL)
```

Arguments

DT	input data.table
projection	PROJ.4 character string
id	Character string of ID column name
coords	Character vector of X coordinate and Y coordinate column names
sortBy	Character string of date time column(s) to sort rows by. Must be a POSIXct.
splitBy	(optional) character string or vector of grouping column name(s) upon which the grouping will be calculated

Details

The DT must be a `data.table`. If your data is a `data.frame`, you can convert it by reference using `data.table::setDT`.

The `id`, `coords`, `sortBy` (and optional `splitBy`) arguments expect the names of respective columns in DT which correspond to the individual identifier, X and Y coordinates, sorting column, and additional splitting columns.

The projection expects a PROJ.4 character string (such as those available on spatialreference.org).

The `sortBy` is used to order the input `data.table` when creating `SpatialLines`. It must be a `POSIXct` to ensure the rows are sorted by date time.

The `splitBy` argument offers further control building `SpatialLines`. If in your DT, you have multiple temporal groups (e.g.: years) for example, you can provide the name of the column which identifies them and build `SpatialLines` for each individual in each year.

`build_lines` is used by `group_lines` for grouping overlapping lines created from relocations.

Value

`build_lines` returns a `SpatialLines` object with a line for each individual (and optionally `splitBy` combination).

An error is returned when an individual has less than 2 relocations, making it impossible to build a line.

See Also

[group_lines](#)

Other Build functions: [build_polys](#)

Examples

```
# Load data.table
library(data.table)

# Read example data
DT <- fread(system.file("extdata", "DT.csv", package = "spatsoc"))

# Cast the character column to POSIXct
DT[, datetime := as.POSIXct(datetime, tz = 'UTC')]

# Proj4 string for example data
utm <- '+proj=utm +zone=36 +south +ellps=WGS84 +datum=WGS84 +units=m +no_defs'

# Build lines for each individual
build_lines(DT, projection = utm, id = 'ID', coords = c('X', 'Y'),
            sortBy = 'datetime')

# Build lines for each individual by year
DT[, yr := year(datetime)]
build_lines(DT, projection = utm, id = 'ID', coords = c('X', 'Y'),
```

```
sortBy = 'datetime', splitBy = 'yr')
```

 build_polys

Build Polygons

Description

build_polys creates a SpatialPolygons object from a data.table. The function accepts a data.table with relocation data, individual identifiers, a projection, hrType and hrParams. The relocation data is transformed into SpatialPolygons for each individual and optionally, each splitBy. Relocation data should be in two columns representing the X and Y coordinates.

Usage

```
build_polys(DT = NULL, projection = NULL, hrType = NULL,
            hrParams = NULL, id = NULL, coords = NULL, splitBy = NULL,
            spPts = NULL)
```

Arguments

DT	input data.table
projection	PROJ.4 character string
hrType	type of HR estimation, either 'mcp' or 'kernel'
hrParams	a named list of parameters for adehabitatHR functions
id	Character string of ID column name
coords	Character vector of X coordinate and Y coordinate column names
splitBy	(optional) character string or vector of grouping column name(s) upon which the grouping will be calculated
spPts	alternatively, provide solely a SpatialPointsDataFrame with one column representing the ID of each point.

Details

The DT must be a data.table. If your data is a data.frame, you can convert it by reference using `data.table::setDT`.

The id, coords (and optional splitBy) arguments expect the names of respective columns in DT which correspond to the individual identifier, X and Y coordinates, and additional grouping columns.

The projection expects a PROJ.4 character string (such as those available on spatialreference.org). build_polys expects planar coordinates (not unprojected latitude, longitude).

The hrType must be either one of "kernel" or "mcp". The hrParams must be a named list of arguments matching those of adehabitatHR::kernelUD and adehabitatHR::getverticeshr or adehabitatHR::mcp.

The `splitBy` argument offers further control building `SpatialPolygons`. If in your `DT`, you have multiple temporal groups (e.g.: years) for example, you can provide the name of the column which identifies them and build `SpatialPolygons` for each individual in each year.

`group_polys` uses `build_polys` for grouping overlapping polygons created from relocations.

Value

`build_polys` returns a `SpatialPolygons` object with a polygon for each individual (and optionally `splitBy` combination).

An error is returned when `hrParams` do not match the arguments of the `hrType` `adehabitathr` function.

See Also

[group_polys](#)

Other Build functions: [build_lines](#)

Examples

```
# Load data.table
library(data.table)

# Read example data
DT <- fread(system.file("extdata", "DT.csv", package = "spatsoc"))

# Cast the character column to POSIXct
DT[, datetime := as.POSIXct(datetime, tz = 'UTC')]

# Proj4 string for example data
utm <- '+proj=utm +zone=36 +south +ellps=WGS84 +datum=WGS84 +units=m +no_defs'

# Build polygons for each individual using kernelUD and getverticeshr
build_polys(DT, projection = utm, hrType = 'kernel',
            hrParams = list(grid = 60, percent = 95),
            id = 'ID', coords = c('X', 'Y'))

# Build polygons for each individual by year
DT[, yr := year(datetime)]
build_polys(DT, projection = utm, hrType = 'mcp', hrParams = list(percent = 95),
            id = 'ID', coords = c('X', 'Y'), splitBy = 'yr')

# Build polygons from SpatialPointsDataFrame
library(sp)
pts <- SpatialPointsDataFrame(coords = DT[, .(X, Y)],
                             proj4string = CRS(utm),
                             data = DT[, .(ID)])

)

build_polys(spPts = pts, hrType = 'mcp', hrParams = list(percent = 95))
```

DT *Movement of 10 "Newfoundland Bog Cows"*

Description

A dataset containing the GPS relocations of 10 individuals in winter 2016-2017.

Format

A data.table with 14297 rows and 5 variables:

ID individual identifier

X X coordinate of the relocation (UTM 21N)

Y Y coordinate of the relocation (UTM 21N)

datetime character string representing the date time

population sub population within the individuals

Examples

```
# Load data.table
library(data.table)

# Read example data
DT <- fread(system.file("extdata", "DT.csv", package = "spatsoc"))
```

get_gbi *Generate group by individual matrix*

Description

get_gbi generates a group by individual matrix. The function accepts a data.table with individual identifiers and a group column. The group by individual matrix can then be used to build a network using [asnipe::get_network](#).

Usage

```
get_gbi(DT = NULL, group = "group", id = NULL)
```

Arguments

DT	input data.table
group	Character string of group column (generated from one of spatsoc's spatial grouping functions)
id	Character string of ID column name

Details

The DT must be a `data.table`. If your data is a `data.frame`, you can convert it by reference using `data.table::setDT`.

The `group` argument expects the name of a column which corresponds to an integer group identifier (generated by `spatsoc`'s grouping functions).

The `id` argument expects the name of a column which corresponds to the individual identifier.

Value

`get_gbi` returns a group by individual matrix (columns represent individuals and rows represent groups).

Note that `get_gbi` is identical in function for turning the outputs of `spatsoc` into social networks as `asnipe::get_group_by_individual` but is more efficient thanks to `data.table::dcast`.

See Also

[group_pts](#) [group_lines](#) [group_polys](#)

Other Social network tools: [randomizations](#)

Examples

```
# Load data.table
library(data.table)

# Read example data
DT <- fread(system.file("extdata", "DT.csv", package = "spatsoc"))

# Cast the character column to POSIXct
DT[, datetime := as.POSIXct(datetime, tz = 'UTC')]
DT[, yr := year(datetime)]

utm <- '+proj=utm +zone=36 +south +ellps=WGS84 +datum=WGS84 +units=m +no_defs'

group_polys(DT, area = FALSE, hrType = 'mcp',
            hrParams = list(percent = 95),
            projection = utm, id = 'ID', coords = c('X', 'Y'),
            splitBy = 'yr')

gbiMtrx <- get_gbi(DT = DT, group = 'group', id = 'ID')
```

Description

group_lines groups rows into spatial groups by creating trajectories and grouping based on spatial overlap. The function accepts a data.table with relocation data, individual identifiers and a threshold. The relocation data is transformed into SpatialLines and overlapping SpatialLines are grouped. The threshold argument is used to specify the criteria for distance between lines. Relocation data should be in two columns representing the X and Y coordinates.

Usage

```
group_lines(DT = NULL, threshold = NULL, projection = NULL,
            id = NULL, coords = NULL, timegroup = NULL, sortBy = NULL,
            splitBy = NULL, spLines = NULL)
```

Arguments

DT	input data.table
threshold	The width of the buffer around the lines in the units of the projection. Supply 0 to compare intersection without buffering.
projection	PROJ.4 character string
id	Character string of ID column name
coords	Character vector of X coordinate and Y coordinate column names
timegroup	(optional) timegroup field in the DT upon which the grouping will be calculated
sortBy	Character string of date time column(s) to sort rows by. Must be a POSIXct.
splitBy	(optional) character string or vector of grouping column name(s) upon which the grouping will be calculated
spLines	Alternatively to providing a DT, provide a SpatialLines object created with the sp package. If a spLines object is provided, groups cannot be calculated by a timegroup or splitBy.

Details

The DT must be a data.table. If your data is a data.frame, you can convert it by reference using `data.table::setDT`.

The id, coords, sortBy (and optional timegroup and splitBy) arguments expect the names of respective columns in DT which correspond to the individual identifier, X and Y coordinates, sorting, timegroup (generated by group_times) and additional grouping columns.

The sortBy is used to order the input data.table when creating SpatialLines. It must be a POSIXct to ensure the rows are sorted by date time. The projection expects a PROJ.4 character string (such as those available on spatialreference.org). group_lines expects planar coordinates (not unprojected latitude, longitude).

The threshold must be provided in the units of the coordinates. The threshold can be equal to 0 if strict overlap is required, else it needs to be greater than 0. The coordinates must be planar coordinates (e.g.: UTM). In the case of UTM, a threshold = 50 would indicate a 50m distance threshold.

The `timegroup` argument is optional, but recommended to pair with `group_times`. The intended framework is to group rows temporally with `group_times` then spatially with `group_lines` (or `group_pts`, `group_polys`). With `group_lines`, pick a relevant `group_times` threshold such as '1 day' or '7 days' which is informed by your study species and system.

The `splitBy` argument offers further control over grouping. If within your DT, you have multiple populations, subgroups or other distinct parts, you can provide the name of the column which identifies them to `splitBy`. The grouping performed by `group_lines` will only consider rows within each `splitBy` subgroup.

Value

`group_lines` returns the input DT appended with a group column.

This column represents the spatial (and if `timegroup` was provided - spatiotemporal) group calculated by overlapping lines. As with the other grouping functions, the actual value of `group` is arbitrary and represents the identity of a given group where 1 or more individuals are assigned to a group. If the data was reordered, the group may change, but the contents of each group would not.

A message is returned when a column named `group` already exists in the input DT, because it will be overwritten.

See Also

[build_lines](#) [group_times](#)

Other Spatial grouping: [group_polys](#), [group_pts](#)

Examples

```
# Load data.table
library(data.table)

# Read example data
DT <- fread(system.file("extdata", "DT.csv", package = "spatsoc"))

# Subset only individuals A, B, and C
DT <- DT[ID %in% c('A', 'B', 'C')]

# Cast the character column to POSIXct
DT[, datetime := as.POSIXct(datetime, tz = 'UTC')]

# Proj4 string for example data
utm <- '+proj=utm +zone=36 +south +ellps=WGS84 +datum=WGS84 +units=m +no_defs'

group_lines(DT, threshold = 50, projection = utm, sortBy = 'datetime',
            id = 'ID', coords = c('X', 'Y'))

## Daily movement tracks
# Temporal grouping
group_times(DT, datetime = 'datetime', threshold = '1 day')

# Subset only first 50 days
DT <- DT[timegroup < 25]
```

```
# Spatial grouping
group_lines(DT, threshold = 50, projection = utm,
            id = 'ID', coords = c('X', 'Y'),
            timegroup = 'timegroup', sortBy = 'datetime')

## Daily movement tracks by population
group_lines(DT, threshold = 50, projection = utm,
            id = 'ID', coords = c('X', 'Y'),
            timegroup = 'timegroup', sortBy = 'datetime',
            splitBy = 'population')
```

group_polys

Group Polygons

Description

group_polys groups rows into spatial groups by overlapping polygons (home ranges). The function accepts a data.table with relocation data, individual identifiers and an area argument. The relocation data is transformed into home range SpatialPolygons. If the area argument is FALSE, group_polys returns grouping calculated by overlap. If the area argument is TRUE, the area and proportion of overlap is calculated. Relocation data should be in two columns representing the X and Y coordinates.

Usage

```
group_polys(DT = NULL, area = NULL, hrType = NULL, hrParams = NULL,
            projection = NULL, id = NULL, coords = NULL, splitBy = NULL,
            spPolys = NULL)
```

Arguments

DT	input data.table
area	boolean indicating either overlap group (when FALSE) or area and proportion of overlap (when TRUE)
hrType	type of HR estimation, either 'mcp' or 'kernel'
hrParams	a named list of parameters for adehabitatHR functions
projection	PROJ.4 character string
id	Character string of ID column name
coords	Character vector of X coordinate and Y coordinate column names
splitBy	(optional) character string or vector of grouping column name(s) upon which the grouping will be calculated
spPolys	Alternatively, provide solely a SpatialPolygons object

Details

The DT must be a `data.table`. If your data is a `data.frame`, you can convert it by reference using `data.table::setDT`.

The `id`, `coords` (and optional `splitBy`) arguments expect the names of respective columns in DT which correspond to the individual identifier, X and Y coordinates, and additional grouping columns.

The `projection` expects a PROJ.4 character string (such as those available on spatialreference.org). `group_polys` expects planar coordinates (not unprojected latitude, longitude).

The `hrType` must be either one of "kernel" or "mcp". The `hrParams` must be a named list of arguments matching those of `adehabitatHR::kernelUD` or `adehabitatHR::mcp`.

The `splitBy` argument offers further control over grouping. If within your DT, you have multiple populations, subgroups or other distinct parts, you can provide the name of the column which identifies them to `splitBy`. The grouping performed by `group_polys` will only consider rows within each `splitBy` subgroup.

Value

When `area` is `FALSE`, `group_polys` returns the input DT appended with a `group` column. As with the other grouping functions, the actual value of `group` is arbitrary and represents the identity of a given group where 1 or more individuals are assigned to a group. If the data was reordered, the group may change, but the contents of each group would not. When `area` is `TRUE`, `group_polys` returns a proportional area overlap `data.table`. In this case, `ID` refers to the focal individual of which the total area is compared against the overlapping area of `ID2`.

If `area` is `FALSE`, a message is returned when a column named `group` already exists in the input DT, because it will be overwritten.

See Also

[build_polys_group_times](#)

Other Spatial grouping: [group_lines](#), [group_pts](#)

Examples

```
# Load data.table
library(data.table)

# Read example data
DT <- fread(system.file("extdata", "DT.csv", package = "spatsoc"))

# Cast the character column to POSIXct
DT[, datetime := as.POSIXct(datetime, tz = 'UTC')]

# Proj4 string for example data
utm <- '+proj=utm +zone=36 +south +ellps=WGS84 +datum=WGS84 +units=m +no_defs'

group_polys(DT, area = FALSE, 'mcp', list(percent = 95),
            projection = utm,
            id = 'ID', coords = c('X', 'Y'))
```

```
areaDT <- group_polys(DT, area = TRUE, 'mcp', list(percent = 95),
  projection = utm,
  id = 'ID', coords = c('X', 'Y'))
```

group_pts

*Group Points***Description**

group_pts groups rows into spatial groups. The function accepts a data.table with relocation data, individual identifiers and a threshold argument. The threshold argument is used to specify the criteria for distance between points which defines a group. Relocation data should be in two columns representing the X and Y coordinates.

Usage

```
group_pts(DT = NULL, threshold = NULL, id = NULL, coords = NULL,
  timegroup = NULL, splitBy = NULL)
```

Arguments

DT	input data.table
threshold	distance for grouping points, in the units of the coordinates
id	Character string of ID column name
coords	Character vector of X coordinate and Y coordinate column names
timegroup	(optional) timegroup field in the DT upon which the grouping will be calculated
splitBy	(optional) character string or vector of grouping column name(s) upon which the grouping will be calculated

Details

The DT must be a data.table. If your data is a data.frame, you can convert it by reference using [data.table::setDT](#).

The id, coords (and optional timegroup and splitBy) arguments expect the names of a column in DT which correspond to the individual identifier, X and Y coordinates, timegroup (generated by group_times) and additional grouping columns.

The threshold must be provided in the units of the coordinates. The threshold must be larger than 0. The coordinates must be planar coordinates (e.g.: UTM). In the case of UTM, a threshold = 50 would indicate a 50m distance threshold.

The timegroup argument is optional, but recommended to pair with [group_times](#). The intended framework is to group rows temporally with [group_times](#) then spatially with group_pts (or [group_lines](#), [group_polys](#)).

The splitBy argument offers further control over grouping. If within your DT, you have multiple populations, subgroups or other distinct parts, you can provide the name of the column which identifies them to splitBy. The grouping performed by group_pts will only consider rows within each splitBy subgroup.

Value

group_pts returns the input DT appended with a group column.

This column represents the spatial (and if timegroup was provided - spatiotemporal) group. As with the other grouping functions, the actual value of group is arbitrary and represents the identity of a given group where 1 or more individuals are assigned to a group. If the data was reordered, the group may change, but the contents of each group would not.

A message is returned when a column named group already exists in the input DT, because it will be overwritten.

See Also

[group_times](#)

Other Spatial grouping: [group_lines](#), [group_polys](#)

Examples

```
# Load data.table
library(data.table)

# Read example data
DT <- fread(system.file("extdata", "DT.csv", package = "spatsoc"))

# Cast the character column to POSIXct
DT[, datetime := as.POSIXct(datetime, tz = 'UTC')]

# Temporal grouping
group_times(DT, datetime = 'datetime', threshold = '20 minutes')
# Spatial grouping with timegroup
group_pts(DT, threshold = 5, id = 'ID',
          coords = c('X', 'Y'), timegroup = 'timegroup')

# Spatial grouping with timegroup and splitBy on population
group_pts(DT, threshold = 5, id = 'ID', coords = c('X', 'Y'),
          timegroup = 'timegroup', splitBy = 'population')
```

group_times

Group Times

Description

group_times groups rows into time groups. The function accepts date time formatted data and a threshold argument. The threshold argument is used to specify a time window within which rows are grouped.

Usage

```
group_times(DT = NULL, datetime = NULL, threshold = NULL)
```

Arguments

DT	input data.table
datetime	name of date time column(s). either 1 POSIXct or 2 IDate and ITime. e.g.: 'datetime' or c('idate', 'itime')
threshold	threshold for grouping times. e.g.: '2 hours', '10 minutes', etc. if not provided, times will be matched exactly. Note that provided threshold must be in the expected format: '## unit'

Details

The DT must be a data.table. If your data is a data.frame, you can convert it by reference using `data.table::setDT`.

The datetime argument expects the name of a column in DT which is of type POSIXct or the name of two columns in DT which are of type IDate and ITime.

threshold must be provided in units of minutes, hours or days. The character string should start with an integer followed by a unit, separated by a space. It is interpreted in terms of 24 hours which poses the following limitations:

- minutes, hours and days cannot be fractional
- minutes must divide evenly into 60
- minutes must not exceed 60
- minutes, hours which are nearer to the next day, are grouped as such
- hours must divide evenly into 24
- multi-day blocks should divide into the range of days, else the blocks may not be the same length

In addition, the threshold is considered a fixed window throughout the time series and the rows are grouped to the nearest interval.

If threshold is NULL, rows are grouped using the datetime column directly.

Value

group_times returns the input DT appended with a timegroup column and additional temporal grouping columns to help investigate, troubleshoot and interpret the timegroup.

The actual value of timegroup is arbitrary and represents the identity of a given timegroup which 1 or more individuals are assigned to. If the data was reordered, the group may change, but the contents of each group would not.

The temporal grouping columns added depend on the threshold provided:

- threshold with unit minutes: "minutes" column added identifying the nearest minute group for each row.
- threshold with unit hours: "hours" column added identifying the nearest hour group for each row.
- threshold with unit days: "block" columns added identifying the multiday block for each row.

A message is returned when any of these columns already exist in the input DT, because they will be overwritten.

See Also

[group_pts](#) [group_lines](#) [group_polys](#)

Examples

```
# Load data.table
library(data.table)

# Read example data
DT <- fread(system.file("extdata", "DT.csv", package = "spatsoc"))

# Cast the character column to POSIXct
DT[, datetime := as.POSIXct(datetime, tz = 'UTC')]

group_times(DT, datetime = 'datetime', threshold = '5 minutes')

group_times(DT, datetime = 'datetime', threshold = '2 hours')

group_times(DT, datetime = 'datetime', threshold = '10 days')
```

randomizations

Data-stream randomizations

Description

randomizations performs data-stream social network randomization. The function accepts a data.table with relocation data, individual identifiers and a randomization type. The data.table is randomized either using step or daily between-individual methods, or within-individual daily trajectory method described by Spiegel et al. (2016).

Usage

```
randomizations(DT = NULL, type = NULL, id = NULL, group = NULL,
  coords = NULL, datetime = NULL, splitBy = NULL,
  iterations = NULL)
```

Arguments

DT	input data.table
type	one of 'daily', 'step' or 'trajectory' - see details
id	Character string of ID column name
group	generated from spatial grouping functions - see details
coords	Character vector of X coordinate and Y coordinate column names

<code>datetime</code>	field used for providing date time or time group - see details
<code>splitBy</code>	List of fields in DT to split the randomization process by
<code>iterations</code>	The number of iterations to randomize

Details

The DT must be a `data.table`. If your data is a `data.frame`, you can convert it by reference using `data.table::setDT`.

Three randomization types are provided:

1. `step` - randomizes identities of relocations between individuals within each time step.
2. `daily` - randomizes identities of relocations between individuals within each day.
3. `trajectory` - randomizes daily trajectories within individuals (Spiegel et al. 2016).

Depending on the type, the `datetime` must be a certain format:

- `step` - `datetime` is integer group created by `group_times`
- `daily` - `datetime` is POSIXct format
- `trajectory` - `datetime` is POSIXct format

The `id`, `datetime`, (and optional `splitBy`) arguments expect the names of respective columns in DT which correspond to the individual identifier, date time, and additional grouping columns. The `coords` argument is only required when the type is "trajectory", since the coordinates are required for recalculating spatial groups with `group_pts`, `group_lines` or `group_polys`.

Please note that if the data extends over multiple years, a column indicating the year should be provided to the `splitBy` argument. This will ensure randomizations only occur within each year.

The `group` argument is expected only when type is 'step' or 'daily'.

For example, using `data.table::year`:

```
DT[, yr := year(datetime)]
randomizations(DT, type = 'step', id = 'ID', datetime = 'timegroup', splitBy = 'yr')
```

`iterations` is set to 1 if not provided. Take caution with a large value for `iterations` with large input DT.

Value

`randomizations` returns the random date time or random id along with the original DT, depending on the randomization type. The length of the returned `data.table` is the original number of rows multiplied by the number of iterations + 1. For example, 3 iterations will return 4x - one observed and three randomized.

Two columns are always returned:

- `observed` - if the rows represent the observed (TRUE/FALSE)
- `iteration` - iteration of rows (where 0 is the observed)

In addition, depending on the randomization type, random ID or random date time columns are returned:

- step - randomID each time step
- daily - randomID for each day and jul indicating julian day
- trajectory - a random date time ("random" prefixed to datetime argument), observed jul and randomJul indicating the random day relocations are swapped to.

References

<http://onlinelibrary.wiley.com/doi/10.1111/2041-210X.12553/full>

See Also

Other Social network tools: [get_gbi](#)

Examples

```
# Load data.table
library(data.table)

# Read example data
DT <- fread(system.file("extdata", "DT.csv", package = "spatsoc"))

# Date time columns
DT[, datetime := as.POSIXct(datetime)]
DT[, yr := year(datetime)]

# Temporal grouping
group_times(DT, datetime = 'datetime', threshold = '5 minutes')

# Spatial grouping with timegroup
group_pts(DT, threshold = 5, id = 'ID', coords = c('X', 'Y'), timegroup = 'timegroup')

# Randomization: step
randStep <- randomizations(
  DT,
  type = 'step',
  id = 'ID',
  group = 'group',
  datetime = 'timegroup',
  splitBy = 'yr',
  iterations = 2
)

# Randomization: daily
randDaily <- randomizations(
  DT,
  type = 'daily',
  id = 'ID',
  group = 'group',
  datetime = 'datetime',
```

```
    splitBy = 'yr',
    iterations = 2
  )

# Randomization: trajectory
randTraj <- randomizations(
  DT,
  type = 'trajectory',
  id = 'ID',
  group = NULL,
  coords = c('X', 'Y'),
  datetime = 'datetime',
  splitBy = 'yr',
  iterations = 2
)
```

spatsoc

spatsoc

Description

spatsoc is an R package for detecting spatial and temporal groups in GPS relocations. It can be used to convert GPS relocations to gambit-of-the-group format to build proximity-based social networks. In addition, the randomization function provides data-stream randomization methods suitable for GPS data.

Details

The spatsoc package provides one temporal grouping function:

- [group_times](#)

three spatial grouping functions:

- [group_pts](#)
- [group_lines](#)
- [group_polys](#)

and two social network functions:

- [randomizations](#)
- [get_gbi](#)

Author(s)

Maintainer: Alec L. Robitaille <robit.alec@gmail.com> (0000-0002-4706-1762)

Authors:

- Quinn Webber (0000-0002-0434-9360)
- Eric Vander Wal (0000-0002-8534-4317)

See Also

Useful links:

- <https://spatsoc.gitlab.io>
- <https://github.com/ropensci/spatsoc>
- Report bugs at <https://github.com/ropensci/spatsoc/issues>

Index

`_PACKAGE` (spatsoc), 18

`asnipe::get_group_by_individual`, 7
`asnipe::get_network`, 6

`build_lines`, 2, 5, 9
`build_polys`, 3, 4, 11

`data.table::dcast`, 7
`data.table::setDT`, 3, 4, 7, 8, 11, 12, 14, 16
`data.table::year`, 16
DT, 6

`get_gbi`, 6, 17, 18
`group_lines`, 3, 7, 7, 11–13, 15, 18
`group_polys`, 5, 7, 9, 10, 12, 13, 15, 18
`group_pts`, 7, 9, 11, 12, 15, 18
`group_times`, 9, 11–13, 13, 18

randomizations, 7, 15, 18

spatsoc, 7, 18
spatsoc-package (spatsoc), 18