

Package ‘supc’

August 26, 2018

Type Package

Title The Self-Updating Process Clustering Algorithms

Version 0.2.1

Maintainer Wush Wu <wush978@gmail.com>

Description Implements the self-updating process clustering algorithms proposed in Shiu and Chen (2016) <doi:10.1080/00949655.2015.1049605>.

URL <https://github.com/wush978/supc>

License GPL (>= 3)

LazyData TRUE

Depends R (>= 3.0.2)

Imports stats, Rcpp

Suggests amap, knitr, rmarkdown, fields, dbscan

LinkingTo Rcpp(>= 0.12), BH(>= 1.62)

VignetteBuilder knitr, rmarkdown

RoxygenNote 6.0.1

SystemRequirements C++11

Encoding UTF-8

NeedsCompilation yes

Author Wush Wu [aut, cre],
Shang-Ying Shiu [aut, ctb]

Repository CRAN

Date/Publication 2018-08-26 18:20:03 UTC

R topics documented:

| | |
|--------------------------------|---|
| D31 | 2 |
| dist.mode | 2 |
| dist.parallelization | 3 |
| freq.poly | 3 |

| | |
|--------------------------|---|
| freq.poly.supc | 4 |
| golub | 4 |
| plot.supc | 5 |
| shape | 5 |
| supc.random | 6 |
| supc1 | 9 |

| | |
|--------------|-----------|
| Index | 12 |
|--------------|-----------|

| | |
|-----|---|
| D31 | <i>The Artificial Data of Consisting of as Many as 31 Randomly Placed Gaussian Clusters</i> |
|-----|---|

Description

This artificial data was generated to show the strength of SUPC. Clustering D31 dataset is difficult for the partition type of clustering algorithms that require an initial set. However, SUP correctly identifies the 31 major clusters.

References

Veenman, C. J., M. J. T. Reinders, and E. Backer. 2002. A Maximum Variance Cluster Algorithm. *IEEE Trans. Pattern Analysis and Machine Intelligence* 24 (9): 1273–80.

| | |
|-----------|---|
| dist.mode | <i>Configure which package is used to compute the distance matrix</i> |
|-----------|---|

Description

Configure which package is used to compute the distance matrix or register one. Note that the speed depends on the data and the hardware.

Usage

```
dist.mode(mode = c("stats", "amap"), FUN = NULL)
```

Arguments

| | |
|------|---|
| mode | string. The available modes are "stats" and "amap" by default. |
| FUN | a function which has one argument x or NULL. The function should compute the pairwise distance of x and return a dist object. The user can skip this argument if the mode is registered. For example, "stats" and "amap" are registered by default. |

Examples

```
# use stats::dist to compute the pairwise distance
dist.mode("stats")
## use gputools to compute the pairwise distance with GPU
# dist.mode("gputools", function(x) gputools::gpuDist(x, method = "euclidean", p = 2.0))
```

dist.parallelization *Configure how many cores will be used to calculate the distance matrix*

Description

Only affect [Dist](#).

Usage

```
dist.parallelization(i)
```

Arguments

i integer.

freq.poly *Plot the frequency polygon of pairwise distance*

Description

Plot the frequency polygon of the pairwise distance.

Usage

```
freq.poly(x, ...)
```

Arguments

x either dist object or matrix.
... other parameters to be passed through to [hist](#).

| | |
|----------------|--|
| freq.poly.supc | <i>Plot the frequency polygon of pairwise distance</i> |
|----------------|--|

Description

Plot the frequency polygon of the pairwise distance. The red dashed line is the used parameter r .

Usage

```
## S3 method for class 'supc'
freq.poly(x, ...)
```

Arguments

| | |
|-----|---|
| x | either dist object or matrix. |
| ... | other parameters to be passed through to hist . |

| | |
|-------|---|
| golub | <i>Gene expression dataset from Golub et al. (1999)</i> |
|-------|---|

Description

Gene expression data (3051 genes and 38 tumor mRNA samples) from the leukemia microarray study of Golub et al. (1999). Each row (gene) is scaled to mean 0 and standard deviation 1.

Value

| | |
|------------|---|
| golub | The matrix of scaled gene expression data. |
| golub.supc | The result of <code>golub.supc <- supc1(golub, r = c(4, 4.3, 4.6, 4.7, 4.8), t = "dynamic")</code> |

References

Golub, T. R., D. K. Slonim, P. Tamayo P., C. Huard C, M. Gaasenbeek M., J.P. J. P. Mesirov, H. H. Coller, et al. 1999. Molecular Classification of Cancer: Class Discovery and Class Prediction by Gene Expression Monitoring. *Science* 286 (5439): 531–37.

| | |
|-----------|--|
| plot.supc | <i>Draw plots of the clustering result</i> |
|-----------|--|

Description

General function to draw plots for analysis

Usage

```
## S3 method for class 'supc'
plot(x, type = "heatmap", ...)
```

Arguments

| | |
|------|---|
| x | supc object to plot. |
| type | character value. <ul style="list-style-type: none"> "heatmap" draw a heatmap to show the result of clustering. The clusters whose size is greater than parameter major.size are treated as major clusters. |
| ... | other parameters to be passed through. |

Examples

```
## Not run:
data(golub, package = "supc")
golub.supc <- supc1(golub, rp = 0.0005, t = "dynamic")
table(golub.supc$size)
plot(golub.supc, type = "heatmap", major.size = 10)

## End(Not run)
```

| | |
|-------|---|
| shape | <i>The Artificial Data of Five Different Clusters</i> |
|-------|---|

Description

This artificial data was generated to have five clusters: one big circle, two small circles, and two ellipses. It was to test if the clustering algorithm could identify and distinguish between the five different clusters or not. The dataset is generated from the following script:

```
makecircle <- function(N, seed) {
  n <- 0
  x <- NULL
  set.seed(seed)
```

```

while(n < N) {
  tmp <- runif(2, min = -1, max = 1)
  if (t(tmp) %*% tmp < 1) {
    n <- n + 1
    x <- rbind(x, tmp)
  }
}
return (x)
}

makedata <- function(n, seed) {
  f <- c(10, 3, 3, 1, 1)
  center <- matrix(
    c(-.3, -.3, -.55, .8, .55, .8, .9, 0, .9, -.6),
    nrow = 5, ncol = 2, byrow = TRUE
  )
  s <- matrix(
    c(.7, .7, .45, .2, .45, .2, .1, .1, .1, .1),
    nrow = 5, ncol = 2, byrow = TRUE
  )
  x <- NULL
  for (i in 1:5) {
    tmp <- makecircle(n * f[i], seed + i)
    tmp[,1] <- tmp[,1] * s[i,1] + center[i,1]
    tmp[,2] <- tmp[,2] * s[i,2] + center[i,2]
    x <- rbind(x, tmp)
  }
  line <- cbind(runif(floor(n / 3), min = -.1, max = .1), rep(.8, floor(n / 3)))
  noise <- matrix(runif(8 * n, min = -1, max = 1), nrow = 4 * n, ncol = 2)
  return(rbind(x, line, noise))
}

shape <- makedata(50, 1000)

```

References

Guha, S., R. Rastogi, and K. Shim. 2001. Cure: An Efficient Clustering Algorithm for Large Databases. *Information Systems* 26 (1): 35–38.

Description

The Randomized Self-Updating Process Clustering (randomized SUP) is a modification of the original SUP algorithm. The randomized SUP randomly generates the partition of the instances during

each iterations. At each iteration, the self updating process is conducted independently in each partition in order to reduce the computation and the memory.

Usage

```
supc.random(x, r = NULL, rp = NULL, t = c("static", "dynamic"),
  k = NULL, groups = NULL, tolerance = 1e-04, cluster.tolerance = 10 *
  tolerance, drop = TRUE, implementation = c("cpp", "R"),
  verbose = (nrow(x) > 10000))
```

Arguments

| | |
|-------------------|---|
| x | data matrix. Each row is an instance of the data. |
| r | numeric vector or NULL. The parameter r of the self-updating process. |
| rp | numeric vector or NULL. If r is NULL, then rp will be used. The corresponding r is the rp -percentile of the pairwise distances of the data. If both r and rp are NULL, then the default value is $rp = c(0.0005, 0.001, 0.01, 0.1, 0.3)$. |
| t | either numeric vector, list of function, or one of "static" or "dynamic". The parameter $T(t)$ of the self-updating process. |
| k | integer value. The number of the partitions. |
| groups | list. The first element is the partition of the first iteration, and the second element is the partition of the second iteration, etc. If the number of the iteration exceeds $\text{length}(\text{groups})$, then new partition will be generated. |
| tolerance | numeric value. The threshold of convergence. |
| cluster.tolerance | numeric value. After iterations, if the distance of two points are smaller than cluster.tolerance , then they are identified as in the same cluster. |
| drop | logical value. Whether to delete the list structure if its length is 1. |
| implementation | either "R" or "cpp". Choose the engine to calculate result. |
| verbose | logical value. Whether to show the iteration history. |

Details

Please check the vignettes via `vignette("supc", package = "supc")` for details.

Value

supc1 returns a list of objects of `class "supc"`.

Each "supc" object contains the following elements:

| | |
|---------|--|
| x | The input matrix. |
| d0 | The pairwise distance matrix of x. |
| r | The value of r of the clustering. |
| t | The function $T(t)$ of the clustering. |
| cluster | The cluster id of each instance. |

| | |
|-----------|--|
| centers | The center of each cluster. |
| size | The size of each cluster. |
| iteration | The number of iterations before convergence. |
| groups | The partition of each iteration. |
| result | The position of data after iterations. |

References

Shiu, Shang-Ying, and Ting-Li Chen. 2016. "On the Strengths of the Self-Updating Process Clustering Algorithm." *Journal of Statistical Computation and Simulation* 86 (5): 1010–1031. doi:10.1080/00949655.2015.1049605. <http://dx.doi.org/10.1080/00949655.2015.1049605>.

Examples

```
## Not run:
# The shape data has a structure of five clusters and a number of noise data points.
makecircle=function(N, seed){
  n=0
  x=matrix(NA, nrow=N, ncol=2)
  while (n<N){
    tmp=runif(2, min=0, max=1)*2-1
    if (sum(tmp^2)<1) {
      n=n+1
      x[n,]=tmp
    }
  }
  return(x)
}

makedata <- function(ns, seed) {
  size=c(10,3,3,1,1)
  mu=rbind(c(-0.3, -0.3), c(-0.55, 0.8), c(0.55, 0.8), c(0.9, 0), c(0.9, -0.6))
  sd=rbind(c(0.7, 0.7), c(0.45, 0.2), c(0.45, 0.2), c(0.1, 0.1), c(0.1, 0.1))
  x=NULL

  for (i in 1:5){
    tmp=makecircle(ns*size[i], seed+i)
    tmp[,1]=tmp[,1]*sd[i,1]+mu[i,1]
    tmp[,2]=tmp[,2]*sd[i,2]+mu[i,2]
    x=rbind(x, tmp)
  }

  tmp=runif(floor(ns/3), min=0, max=1)/5-0.1
  tmp=cbind(tmp, 0.8*rep(1, floor(ns/3)))
  x=rbind(x, tmp)
  x=rbind(x, matrix(1, nrow=2*ns, ncol=2)*2-1)
  return(x)
}

shape1 <- makedata(5000, 1000)
dim(shape1)
```



```

plot(shape1)

X.supc=supc.random(shape1, r=0.5, t="dynamic", k = 500)
plot(shape1, col=X.supc$cluster)

## End(Not run)

```

supc1

Self-Updating Process Clustering

Description

The SUP is a distance-based method for clustering. The idea of this algorithm is similar to gravitational attraction: every sample gravitates towards one another. The algorithm mimics the process of gravitational attraction iteratively that eventually merges the samples into clusters on the sample space. During the iterations, all samples continue moving until the system becomes stable.

Usage

```

supc1(x, r = NULL, rp = NULL, t = c("static", "dynamic"),
      tolerance = 1e-04, cluster.tolerance = 10 * tolerance, drop = TRUE,
      implementation = c("cpp", "R", "cpp2"), verbose = (nrow(x) > 10000))

```

Arguments

| | |
|-------------------|---|
| x | data matrix. Each row is an instance of the data. |
| r | numeric vector or NULL. The parameter r of the self-updating process. |
| rp | numeric vector or NULL. If r is NULL, then rp will be used. The corresponding r is the rp -percentile of the pairwise distances of the data. If both r and rp are NULL, then the default value is $rp = c(0.0005, 0.001, 0.01, 0.1, 0.3)$. |
| t | either numeric vector, list of function, or one of "static" or "dynamic". The parameter $T(t)$ of the self-updating process. |
| tolerance | numeric value. The threshold of convergence. |
| cluster.tolerance | numeric value. After iterations, if the distance of two points are smaller than <code>cluster.tolerance</code> , then they are identified as in the same cluster. |
| drop | logical value. Whether to delete the list structure if its length is 1. |
| implementation | either "R", "cpp" or "cpp2". Choose the engine to calculate result. The "cpp2" parallelly computes the distance in C++ with OpenMP, which is not supported under OS X, and uses the early-stop to speed up calculation. |
| verbose | logical value. Whether to show the iteration history. |

Details

Please check the vignettes via `vignette("supc", package = "supc")` for details.

Value

supc1 returns a list of objects of class "supc".

Each "supc" object contains the following elements:

| | |
|-----------|--|
| x | The input matrix. |
| d0 | The pairwise distance matrix of x or NULL. |
| r | The value of r of the clustering. |
| t | The function $T(t)$ of the clustering. |
| cluster | The cluster id of each instance. |
| centers | The center of each cluster. |
| size | The size of each cluster. |
| iteration | The number of iterations before convergence. |
| result | The position of data after iterations. |

References

Shiu, Shang-Ying, and Ting-Li Chen. 2016. "On the Strengths of the Self-Updating Process Clustering Algorithm." *Journal of Statistical Computation and Simulation* 86 (5): 1010–1031. doi:10.1080/00949655.2015.1049605. <http://dx.doi.org/10.1080/00949655.2015.1049605>.

Examples

```
## Not run:
set.seed(1)
X <- local({
  mu <- list(
    x = c(0, 2, 1, 6, 8, 7, 3, 5, 4),
    y = c(0, 0, 1, 0, 0, 1, 3, 3, 4)
  )
  X <- lapply(1:5, function(i) {
    cbind(rnorm(9, mu$x, 1/5), rnorm(9, mu$y, 1/5))
  })
  X <- do.call(rbind, X)
  n <- nrow(X)
  X <- rbind(X, matrix(0, 20, 2))
  k <- 1
  while(k <= 20) {
    tmp <- c(13*runif(1)-2.5, 8*runif(1)-2.5)
    y1 <- mu$x - tmp[1]
    y2 <- mu$y - tmp[2]
    y <- sqrt(y1^2+y2^2)
    if (min(y)> 2){
      X[k+n,] <- tmp
      k <- k+1
    }
  }
  X
})
```

```
X.supcs <- supc1(X, r = c(0.9, 1.7, 2.5), t = "dynamic")
X.supcs$cluster
plot(X.supcs[[1]], type = "heatmap", major.size = 2)
plot(X.supcs[[2]], type = "heatmap", col = cm.colors(24), major.size = 5)

X.supcs <- supc1(X, r = c(1.7, 2.5), t = list(
  function(t) {1.7 / 20 + exp(t) * (1.7 / 50)},
  function(t) {exp(t)}
))
plot(X.supcs[[1]], type = "heatmap", major.size = 2)
plot(X.supcs[[2]], type = "heatmap", col = cm.colors(24), major.size = 5)

## End(Not run)
```

Index

class, [7](#), [10](#)

D31, [2](#)

Dist, [3](#)

dist.mode, [2](#)

dist.parallelization, [3](#)

freq.poly, [3](#)

freq.poly.subclist (freq.poly.supc), [4](#)

freq.poly.supc, [4](#)

golub, [4](#)

hist, [3](#), [4](#)

plot.supc, [5](#)

shape, [5](#)

supc.random, [6](#)

supc1, [9](#)