

Package ‘wowa’

February 5, 2021

Type Package

Title Weighted Ordered Weighted Average

Version 1.0.1

Date 2021-02-01

Maintainer Gleb Beliakov <gleb@deakin.edu.au>

Author Gleb Beliakov [aut, cre],
Daniela Calderon [aut]

Description

Introduce weights into Ordered Weighted Averages and extend bivariate means based on n-ary tree construction. Please refer to the following:

G. Beliakov, H. Bustince, and T. Calvo (2016, ISBN: 978-3-319-24753-3),

G. Beliakov(2018) <doi:10.1002/int.21913>,

G. Beliakov, J.J. Dujmovic (2016) <doi:10.1016/j.ins.2015.10.040>,

J.J. Dujmovic and G. Beliakov (2017) <doi:10.1002/int.21828>.

License LGPL-3

LazyData TRUE

Imports Rcpp (>= 1.0.0)

LinkingTo Rcpp

RoxygenNote 5.0.1

NeedsCompilation yes

Copyright Gleb Beliakov

Repository CRAN

Date/Publication 2021-02-05 09:40:02 UTC

R topics documented:

| | |
|-----------------------------|---|
| wowa | 2 |
| wowa.ImplicitWOWA | 3 |
| wowa.OWA | 3 |
| wowa.WAM | 4 |
| wowa.WAn | 5 |

| | |
|---|---|
| wowa.weightedOWAQuantifier | 6 |
| wowa.weightedOWAQuantifierBuild | 7 |
| wowa.WOWATree | 7 |

| | |
|--------------|----------|
| Index | 9 |
|--------------|----------|

| | |
|------|---------------------|
| wowa | <i>WOWA package</i> |
|------|---------------------|

Description

Various weighted multivariate extensions of bivariate and OWA functions, including implicit, quantifier-based and binary tree based WOWA.

Usage

wowa()

Details

Lists the functions implemented in this package.

Value

No return value, called for printing only.

Author(s)

Gleb Beliakov, Daniela L. Calderon, Deakin University

References

- [1]G. Beliakov, H. Bustince, and T. Calvo. A Practical Guide to Averaging Functions. Springer, Berlin, Heidelberg, 2016.
- [2]G. Beliakov. A method of introducing weights into OWA operators and other symmetric functions. In V. Kreinovich, editor, Uncertainty Modeling. Dedicated to B. Kovalerchuk, pages 37-52. Springer, Cham, 2017.
- [3]G. Beliakov. Comparing apples and oranges: The weighted OWA function, Int.J. Intelligent Systems, 33, 1089-1108, 2018.
- [4]V. Torra. The weighted OWA operator. Int. J. Intelligent Systems, 12:153-166, 1997.
- [5]G. Beliakov and J.J. Dujmovic , Extension of bivariate means to weighted means of several arguments by using binary trees, Information sciences, 331, 137-147, 2016.
- [6] J.J. Dujmovic and G. Beliakov. Idempotent weighted aggregation based on binary aggregation trees. Int. J. Intelligent Systems 32, 31-50, 2017.

Examples

wowa()

wowa.ImplicitWOWA *Implicit Weighted OWA Computation Function*

Description

Function for Calculating implicit Weighted OWA function

Usage

```
wowa.ImplicitWOWA(x, p, w, n)
```

Arguments

| | |
|---|---------------------------|
| x | The vector of inputs |
| p | The weights of inputs x |
| w | The OWA weightings vector |
| n | Dimension of the vector x |

Value

output The value of the Implicit Weighted OWA

Author(s)

Gleb Beliakov, Daniela L. Calderon, Deakin University

Examples

```
n <- 4
example <- wowa.ImplicitWOWA(c(0.3,0.4,0.8,0.2), c(0.3,0.25,0.3,0.15),
                             c(0.4,0.35,0.2,0.05), n)
example
```

wowa.OWA *Ordered weighted average function*

Description

Function for computing the ordered weighted averages

Usage

```
wowa.OWA(n, x, w)
```

Arguments

| | |
|---|---------------------------|
| n | Dimension of the vector x |
| x | The vector of inputs |
| w | The OWA weights |

Value

| | |
|--------|--|
| output | The value of the ordered weighted average. |
|--------|--|

Author(s)

Gleb Beliakov, Daniela L. Calderon, Deakin University

Examples

```
n <- 4
wowa.OWA(n, c(0.3,0.4,0.8,0.2), c(0.4,0.35,0.2,0.05))
```

wowa.WAM

WAM computation

Description

Function for calculating the Weighted Arithmetic Mean

Usage

```
wowa.WAM(n, x, w)
```

Arguments

| | |
|---|--------------------------|
| n | Dimension of the array x |
| x | The vector of inputs |
| w | The vector of weights |

Value

| | |
|--------|-------------------------------|
| output | The value of the WAM function |
|--------|-------------------------------|

Author(s)

Gleb Beliakov, Daniela L. Calderon, Deakin University

Examples

```
n <- 4
wowa.WAM(n, c(0.3,0.4,0.8,0.2), c(0.3,0.25,0.3,0.15) )
```

`wowa.WAn`*Extension of binary averaging*

Description

Function for calculating a binary tree multivariate extension of a binary averaging function

Usage

```
wowa.WAn(x, w, n, Fn, L)
```

Arguments

| | |
|-----------------|---|
| <code>x</code> | Vector of inputs |
| <code>w</code> | The weightings vector |
| <code>n</code> | Dimension of the array <code>x</code> (and <code>w</code>) |
| <code>Fn</code> | Bivariate symmetric mean that is extended to <code>n</code> arguments |
| <code>L</code> | The number of levels of the binary tree (see docs) |

Value

| | |
|---------------------|---|
| <code>output</code> | The output is Weighted <code>n</code> -variate mean extending <code>Fn</code> |
|---------------------|---|

Author(s)

Gleb Beliakov, Daniela L. Calderon, Deakin University

Examples

```
Fn <- function( x, y) { # just a simple arithmetic mean,
# but can be more complex functions (eg heronian, Logarithmic means)
out <- (x+y)/2
return(out)
}

n <- 4
example <- wowa.WAn(c(0.3,0.4,0.8,0.2), c(0.4,0.3,0.2,0.1), n, Fn, 10)
example
```

`wowa.weightedOWAQuantifier`*WOWA value computation Function*

Description

Function for calculating the value of the quantifier-based WOWA function

Usage

```
wowa.weightedOWAQuantifier(x, p, w, n, spl)
```

Arguments

| | |
|------------------|---|
| <code>x</code> | The vector of inputs |
| <code>p</code> | The weights of inputs <code>x</code> |
| <code>w</code> | The OWA weightings vector |
| <code>n</code> | The dimension of the array <code>x</code> |
| <code>spl</code> | A structure that keeps the spline knots and coefficients computed in <code>weightedOWAQuantifierBuild</code> function |

Value

| | |
|---------------------|---|
| <code>output</code> | The output is quantifier-based WOWA value |
|---------------------|---|

Author(s)

Gleb Beliakov, Daniela L. Calderon, Deakin University

Examples

```
n <- 4
pweights=c(0.3,0.25,0.3,0.15);
wweights=c(0.4,0.35,0.2,0.05);
tempspline <- wowa.weightedOWAQuantifierBuild(pweights,wweights , n)
wowa.weightedOWAQuantifier(c(0.3,0.4,0.8,0.2), pweights, wweights, n, tempspline)
```

wowa.weightedOWAQuantifierBuild
RIM quantifier of the Weighted OWA function

Description

Function for building the RIM quantifier of the Weighted OWA function

Usage

```
wowa.weightedOWAQuantifierBuild(p, w, n)
```

Arguments

| | |
|---|----------------------------------|
| p | The weights of inputs x |
| w | The OWA weightings vector |
| n | The dimension of the vectors p,w |

Value

| | |
|--------|---|
| output | A structure which has fields: spl, which keeps the spline knots and coefficients for later use in weightedOWAQuantifier, and Tnum, the number of knots in the monotone spline |
|--------|---|

Author(s)

Gleb Beliakov, Daniela L. Calderon, Deakin University

Examples

```
n <- 4
pweights=c(0.3,0.25,0.3,0.15);
wweights=c(0.4,0.35,0.2,0.05);
tspline <- wowa.weightedOWAQuantifierBuild(pweights,wweights , n)
wowa.weightedOWAQuantifier(c(0.3,0.4,0.8,0.2), pweights, wweights, n, tspline)
```

wowa.WOWATree *Weighted extension of the OWA function*

Description

Function for extending order weighted averages and other multivariate symmetric functions

Usage

```
wowa.WOWATree(x, p, w, n, Fn, L)
```

Arguments

| | |
|----|---|
| x | The vector of inputs |
| p | The weights of inputs x |
| w | The OWA weightings vector |
| n | The dimension of the vector x |
| Fn | Base n-variate symmetric function defined in R |
| L | The number of levels of the n-ary tree (see docs) |

Value

| | |
|--------|--|
| output | The output is the weighted ordered weighted average. |
|--------|--|

Author(s)

Gleb Beliakov, Daniela L. Calderon, Deakin University

Examples

```
Fn <- function(n, x, w) {
  out <- 0.0
  for(i in 1:n) out<- out+x[i]*w[i];
  #print(out)
  return(out)
}
n <- 4

example <- wowa.WOWATree(c(0.3,0.4,0.8,0.2), c(0.3,0.25,0.3,0.15),
  c(0.4,0.35,0.2,0.05), n, Fn, 10)

example
```


Index

- * **Implicit WOWA**
 - wowa.ImplicitWOWA, 3
 - * **OWA**
 - wowa.OWA, 3
 - * **WAM**
 - wowa.WAM, 4
 - * **WAn**
 - wowa.WAn, 5
 - * **WOWATree**
 - wowa.WOWATree, 7
 - * **WOWA**
 - wowa, 2
 - wowa.ImplicitWOWA, 3
 - wowa.WAM, 4
 - wowa.WAn, 5
 - wowa.weightedOWAQuantifier, 6
 - wowa.weightedOWAQuantifierBuild, 7
 - * **weightedOWAQuantifier**
 - wowa.weightedOWAQuantifier, 6
 - wowa.weightedOWAQuantifierBuild, 7
 - * **weightedf**
 - wowa.WOWATree, 7
 - * **wowa**
 - wowa, 2
- wowa, 2
wowa.ImplicitWOWA, 3
wowa.OWA, 3
wowa.WAM, 4
wowa.WAn, 5
wowa.weightedOWAQuantifier, 6
wowa.weightedOWAQuantifierBuild, 7
wowa.WOWATree, 7